

SOLARFOX® SF-100 SERIES - TECHNICAL DATA



The SF-100 series is designed for indoor installation and sets itself apart through robust hardware and a basic range of functions. The displays can be operated up to 10 hours daily or turned on and off via a time switch function (SF-100 32").

- LED display
- Built-in control computer SC-100 with software
- 15° tilting wall mount
- Cable and accessories
- Individual content and design
- Internet connection (LAN, opt. WIFI, 3G with ext. router)
- Online management

Product description	SF-100 24"	SF-100 32"
Diagonal measurement	61 cm (24")	81 cm (32")
Dimensions (L x D x H) incl. wall mount	55.4 x 7.9 x 33.2 cm	74 x 13.5 x 43,5 cm
Power consumption during operation	20-24 W	35-50 W
Energy efficiency class	A	B
Weight	3.5 kg	6.5 kg
Colour	Black	Black
Technology	IPS/LED	IPS/LED
Resolution	1920 x 1080	1366 x 768
Service life	50.000 h	30.000 h
Brightness	250 cd/m ²	240 cd/m ²
Viewing angle	178 degrees	178 degrees
Operating time	10/7	10/7
Display format	1080p (FullHD)	720p (HD-ready)
Video input formats	720p, 1080i, 1080p	720p
Aspect ratio of the image	16:9	16:9
Video interface	HDMI	HDMI
Other Interfaces	1x VGA, opt. WiFi	opt. WiFi
Time switch (switching on and off)	-	individual day timer
TV tuner	No tuner	Antenna/Cable, DVB-T, DVB-C, DVB-C HD
Speaker system	without speakers	2 Ch Speaker system
Speaker output	Yes, jack	Yes, 2 ports
USB port	Yes, 2	Yes, 1
Remote control	-	Remote control
Power supply	100/240 V	100/240 V
Environmental protection standards	ENERGY STAR	ENERGY STAR
Manufacturer's warranty	3-year warranty	3-year warranty
Packaging (L x D x H)	64 x 15 x 40.7 cm	80 x 14 x 50.5 cm
Package weight	4.4 kg	8 kg